





Static Contour Vinyl Sheet

Contour® ESD

Product Information

Technical Data

Structure 結構	Standard	Unit	Contour ESD
Type of flooring 材料類型	EN 649/EN ISO 10581	-	Static Contour Vinyl Sheet 防靜電捲材
	-	-	
Overall thickness 總厚度	-	mm-	2
Sheet width/length 捲材尺寸		m	2m/15-20m
Safety criteria 安全要求			
Flammability 防火	GB 8624	class 組	B1
Flammability 防火	EN 13501-1	class 組	Bfl-s1
Slip resistance 防滑	DIN 51130/DIN EN 16165	group 組	R9
Performance 性能			
Impact sound reduction 吸音	ISO 10140	db	3
Human Body Walking Voltage 人體行走電壓	IEC 61340-4-5	Lul<100v	conform
Wear resistance 耐磨性	EN 649	group 組	P
Color fastness 色牢度	ISO 105-B02	rating	≥6
Electrical resistance 抗電阻性	EN 1081	Ω	1.0x10 ⁶ -1.0x10 ⁸
Static electrical propensity 靜電測試性能	EN 1815	kV	≤2.0
Thermal resistance 導熱係數	EN 12664	W/m.k	0.06
Resistance to staining 耐阻性	EN 423/EN ISO 26987	-	Good resistance
Castor chair 腳輪測試	ISO 4918		Pass
Classification			
Domestic 家用	ISO 10874-EN 685	class 等級	23 heavy duty
Commercial 商用	ISO874-EN685	class 等級	34 very heavy duty
Industrial 工業	ISO874-EN685	class 等級	43 heavy duty
Additional property			
Castor chair 輪椅滾動  ✓		Antistatic Behaviour 靜電負  荷 ✓	
Underfloor Heating 基層遇熱  ✓		Chemical Resistance 抗酸鹼能力  ✓	